



HRC-P6800Z32T150

●

- 1.
- 2.
- 3.
- 4.

●

- 1.
- 2.
3. 320*240 336*256 384*288 640*512
4. 50mm/75mm/100mm/150mm/185mm
20-100/25-100mm/30-150mm/45-180m m

●

1. 360° -45° ~ +45°
2. GIS
- 3.
4. RS485/RS422/TCP/IP

●

1. RS485/RS422/TCP/IP

| | | | |
|--|--|-----------------------|---------------------|
| | | | |
| | | HRC-P6800Z 32T150R3 | HRC-P6800Z 32T150R6 |
| | | 200 | 1/1.8" CMOS |
| | | 1920*1080 | |
| | | 15.6-500mm | |
| | | 32 | |
| | | 2.8m | |
| | | F2.0-360 | |
| | | | |
| | | 7.5-14μm | |
| | | | |
| | | 384x288 | 640x480 |
| | | 150mm | |
| | | 16 | |
| | | | |
| | | 70kg | |
| | | 360° | -25° 115° |
| | | 0.01°/ | 80°/ |
| | | 0.01°/ | 80°/ |
| | | 256 | |
| | | | |
| | | | |
| | | RS-422 RS-485 TCP/IP | |
| | | PELCO D | |
| | | | |
| | | AC220V ± 20%, 50/60Hz | |
| | | -45 65 | |
| | | | |
| | | 65Kg | 70Kg |
| | | 220W 270W | 230W 280W |
| | | IP67 | |
| | | | |
| | | ±15° | 6 , 0.5° ± 2mrad |
| | | | |
| | | / | |

